



YHZM75 Drum Mobile Concrete Batching Plant

General Parameters

Model	YHZM75	
Capacity	75m ³ /h	
Concrete mixer	JZM1500	
Cycle time	1.5 minutes	
Weighing accuracy	Aggregate	±2%
	Cement	±1%
	Water	±1%
	additive	±1%

Detailed configuration parameters

1. Concrete mixer

Model	JZM1500
Feeding capacity	1600L
Discharge capacity	1000L
Mixing capacity	60m ³ /h
Mixing motor power	11kw*2
Water power	3kw
Mixing time	20s
Discharge height (working condition)	1185mm

2. Aggregate batcher

Model	PLD1600-3
Storage hopper Capacity	7m ³ *3
Weighing hopper capacity	1600L
Motor power	4kw*3
Sand bin vibration motor power	0.37kw*1
Sensor	1000kg*3 拉力 pull
Belt conveyor	500*10500mm*1 ,600*8500mm*1,500*4200m m*1
Feeding height (working condition)	3290mm

3. Weighing Scales

Cement weighing system	Volume of cement weighing hopper	0.6m ³
	Pneumatic butterfly valve	∅ 300

Haomei Machinery Equipment Co.,Ltd

ADD.: NO.14 Waihuan Road, New district, Zhengzhou, Henan,China

Mobile:0086-18137889531

E-mail:nydia@concretebatchplant24.com

Tel.: +86-371-65621392

Web: www.concrete-mix-plant.com

	Sensor	500kg*3
Water weighing system	Volume of water weighing bucket	0.4m ³
	Water Pump power	1.5kw
	Pneumatic butterfly valve	∅ 80
	Sensor	300kg*3
Additive weighing system	Volume of additive weighing bucket	0.03m ³
	Pneumatic valve	∅ 50
	Sensor	50kg*1

4. Pneumatic system

Air compressor	0.6m ³
cylinder	AKS

5. Control system

Strong and weak current cabinet	Integrated strong and weak current cabinet
---------------------------------	--

6. Mobile chassis

Size of mixing plant chassis	10.92M*2M
Tyre type and quantity	∅ 1100mm*8

